STELVIO



THE
NEVER-ENDING
JOURNEY



MOTOGUZZI.CO.ID

STELVIO

MOTO GUZZI STELVIO ARAS TECHNICAL SHEET

Engine	Transversal 90° V-Twin, four valves per cylinder, liquid cooled with Ride by Wire
Displacement	1042 сс
Bore x Stroke	96 X 72 mm
Maximum power	115 Hp (84.6 kW) @ 8,700 rpm
Maximum torque	105 Nm @ 6,750 rpm
Gearbox	6 speed
Clutch	Hydraulic
Front suspension	Sachs Ø 46 mm USD fork with adjustable preload and rebound damping
Rear suspension	KYB monoshock with adjustable preload and rebound damping
Front brake	Twin Ø 320 mm floating discs, 4-piston Brembo monobloc radial calipers
Rear brake	Single Ø 280 mm disc, 2-piston Brembo caliper
Front wheel	Tubeless spoked wheels, 19" x 3.00"
Rear wheel	Tubeless spoked wheels, 17" x 4.50"
Wet weight	246 kg
Fuel tank	20,5
Compliance	Euro 5+

The company reserves the right to make technical and aesthetic modifications at any time. Complete information regarding models and accessories is available at vow.nontoguzzi.co.id. Ride carefully, always wearing a helmet and suitable gear. Always comply with the Highway Code and respect the environment. Read the user and maintenance manuals thoroughly. Always request original, homologated spare parts in accordance with the laws in force. Refer to Official Moto Guzzi Dealers and Authorised Retailers for a secure purchase and guaranteed customer service

COMPANY WITH
ENVIRONMENTAL SYSTEM
CERTIFIED BY DNV
= ISO 14001=

COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV = OHSAS 18001=





FEATURES



ICONIC 90° TRANSVERSE V ENGINE



PFF RIDER ASSISTANCE SOLUTION®



AN UNMISTAKEN DESIGN



COMFORT SUSPENSION

motoguzzi.co.id



