

and on MOTOGUZZI.CO.ID





Engine	Transversal 90° V-twin, two valves per cylinder (titanium intake)
Displacement	853 cc
Cooling	Air
Bore / Stroke	84 mm x 77 mm
Max power	47.8kW (65 HP) at 6,800 rpm
Max torque	73 Nm at 5,000 rpm
Gearbox	6 speed
Front suspension	Hydraulic telescopic fork Ø 40 mm
Rear suspension	Swingarm twin-sided with two spring preload adjustable shock absorbers
Front brake	Stainless steel floating disk Ø 320 mm, brembo caliper with 4 differentiated and opposed pistons
Rear brake	Stainless steel disk Ø 260 mm, Floating 2 pistons caliper
Front wheel	Lightweight alloy, 100/90 - 18"
Rear wheel	Lightweight alloy, 150/70 - 17"
Seat height	780 mm
Dry weight	198 kg
Kerb weight	218 kg (In compliance with VO (EU) 168/2013, with all operating fluids, with standard equipment and fuel tank refilled to at least 90% of usable capacity)
 Fuel tank capacity	21 L (0,5 L reserve)
Compliance	Meets European directive Euro 5











The company reserves the right to make technical and aesthetic modifications at any time. Complete information regarding models and accessories is available at www.motoguzzi.co.id. Ride carefully, always wearing a helmet and suitable gear. Always comply with the Fighwa Code and respect the environment. Read the user and maintenance manuals thoroughly. Always request original, homologated spare partin accordance with the laws in force. Refer to Official Mode Guzz Deleters and Authorises for a secure purchase and guaranteed coateners serving.

PT Piaggio Indonesia customer service: (021) 1500 585, customer service @id.piaggio.com

COMPANY WITH ENVIRONMENTAL SYSTEM CENTIFIED BY DNV ISO 14001 COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV ISO 9001 COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV OHSAS 18001=



