







Engine	Transversal 90° V-twin, two valves per cylinder (titanium intake)
Displacement	853 cc
Cooling	Air
Bore / Stroke	84 mm x 77 mm
Max power	56 kW (76 HP) at 7,500 rpm
Max torque	82 Nm at 5,000 rpm
Gearbox	6 speed
Front suspension	Upside-down hydraulic telescopic fork Ø 41 mm, with adjustable extension and spring pre-load
Rear suspension	Swingarm twin-sided with lateral mono shock absorber, adjustable extension and spring pre-load
Front brake	Double stainless steel floating disk Ø 320 mm, radial Brembo calipers with 4 opposed pistons
Rear brake	Stainless steel disk Ø 260 mm, floating 2 pistons caliper
Front wheel	Cross spoked tubeless wheel, 110/80 - 19"
Rear wheel	Cross spoked tubelesswheel, 150/70 - 17"
Seat height	830 mm
Dry weight	209 kg
Kerb weight	243 kg (according to guidline VO (EU) 168/2013 with all fluids with standard equipment and fuelled with at least 90% of usable tank volume)
Fuel tank capacity	23 L (1 L reserve)
Compliance	Meets European directive Euro 5



The company reserves the right to make techinal and aesthetic modifications at any time. Complete information reparding models and accessories is available at www.motoguzzi.co.id. Ride carefully, always wearing a halmet and suitable gear.

Always comply with the Highwa Code and respect the environment. Read the user and maintenance manuals throughly.

Always request original, homologated spare partin accordance with the faws in force.

Refer to Official Moto Guzzi Dealers and Authorised for a secure purchase and guaranteed customer service.

## PT Piaggio Indonesia customer service: (021) 1500 585, customer service @id.piaggio.com

COMPANY WITH ENVIRONMENTAL SYSTEM CEBTIFIED BY DNV ISO 14001 COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV = ISO 9001= COMPANY WITH SAFETY SYSTEM CERTIFIED BY DNV = OHSAS 18001=

